



Apollo SL5 medium camera option – The ideal LED lamp to include an inconspicuous camera for heightened security.

- Ethernet PoE 12V
- Fiber (external converter)
- WiFi: 2.4 or 5GHz
- LTE
- Built-in recorder with GPS

Technical Specifications

Camera	
Image Sensor	1/2.8" Sony IMX335 CMOS
Effective Pixels	2592(H)×1944 (V)
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto
Other	AGC,2/3 DNR,Motion Detection, Privacy Mask, Mirror, Flip
Encode	
Embedded Solution	Mstar MSC316DM



Video Standard	H.265/H.264
Video Resolution	MainStream:15fps@5MP(2592x1944),25fps@4MP/3MP,30fps@1080P/720P
	Sub stream: D1/VGA(640x480)/360P/QVGA@25fps
Video Bitrates	512Kbps - 6Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a
IR LED	
IR LED	10 Array IR LED
IR Distance	10-15 meters
Lens	
Focal Length	3.6 mm fixed lens
Optional Function	
POE, Audio	
Network Services	
Protocol	RTSP/FTP/DHCP/DDNS/NTP/SMTP/NFS
P2P	YES
Web	IE , firefox 32bit ESR
Media	CMS, Android, IOS
ONVIF	17.06 compatible
General	
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	12 VDC \pm 10%
Power Consumption	< 5 W
Operating Temperature	-30°C-(+60)°C, 10%-90%RH